


Picture may differ from original product

1110-3 Series — Medi Series

PPR Wheel Insert (White Dark Gray) Wheel Diameter×Wheel Width 100×14（60.5） mm

KS-11100402268013 Copy model no.

Wheel Diameter	Load Capacity (Dynamic)	Overall Height	Wheel Bearing
100mm	50kgs	120mm	Wheel With Plain Bearing

- Double brake Casters, Ø11x22L insert rod, C-ring.
- White legs made of reinforced Polypropylene, insert rod Mounting Type.
- Rust-proof, Corrosion resistant, Attractive appearance, Economical, and rotates smoothly.
- High-Quality Impact-Resistant Polypropylene Wheel Center, High-Quality Reinforced Polypropylene Rubber (TPR) Wheel Tread.
- Dark gray, Plain Bearing.
- Wheel tread: Thermoplastic rubber elastomer (TPR)
- Wheel Center: Made of high-quality impact-resistant polypropylene

Product descriptions are for reference only. The actual product shall prevail.

Product Data Sheet (Metric) | 3D Drawing Request

3D drawings are for members only. Please log in to download.

Product Data Sheet

Metric | Imperial

Wheel Diameter	100mm	Wheel Width	60.5mm
Wheel Bearing	Wheel With Plain Bearing	Threaded Stem	Ø11
Threaded Length	22mm	Offset	28mm
Swivel Interference	228mm	Overall Height	120mm
Swivel Radius	114mm	Hardness Of Tread	82±5° Shore A
Load Capacity (Dynamic)	50kgs	Load Capacity (Static)	75kgs
Temperature	-20°C to +60°C	Fork Type	Swivel Caster With Total Brake
Stainless	N/A	Electrical Conductivity	N/A
Anti-Static	N/A	Weight	0.50kgs
Standard	ISO22881		

* For any deviation between metric and imperial spec, please refer to the metric spec.

Performance

Rolling Smoothness
Max. 5 points Score: 4

Quiet Operation
Max. 5 points Score: 4

Floor Surface Preservation
Max. 5 points Score: 5

Downloads

PDF **1110-EN-KS2026041320.pdf**
Product Data Sheet (Metric)

3D **1110-CN-KS2026041320-d261120151118.zip**
3D drawings are for members only. Please log in to download.

Related Products



1110-3 Series — Medi Series

PPR Wheel Insert (White Dark Gray) Wheel Diameter×Wheel Width…

KS-11100402267013

wheel diameter	dynamic load	overall height
100 mm	50 kg	120 mm

View specs →