

Picture may differ from original product




PU Series

Wheel Diameter × Wheel Width 200 x 49mm

YJ-12033308200771 Copy model no.

Wheel Diameter(D)	Load Capacity (Dynamic)	Wheel Bearing
200mm	**700kgs**	**Ball Bearing**

- Excellent Floor Surface Preservation and wear resistance, low noise.
- Excellent Hydrolysis Resistance.
- Suitable for tropical regions and humid working environments.
- PU Red
- Wheel Center: cast iron core
- Wheel Tread: High-quality polyurethane
- Bearing: Ball bearing

Product descriptions are for reference only. The actual product shall prevail.

Product Data Sheet | 3D Drawing Request

3D drawings are for members only. Please log in to download.

Product Data Sheet

Metric | Imperial

Wheel Diameter(D)	**200mm**	Wheel Width(T2)	**49mm**
Wheel Bearing	**Ball Bearing**	Axle Bore(d)	**20mm**
Axle Bore(S)	—	Bearing Bore Depth(t)	—
Hub Lenth(T1)	**50mm**	Hardness Of Tread	**92±5° Shore A**
Load Capacity (Dynamic)	**700kgs**	Load Capacity (Static)	**1050kgs**
Temperature	**-20°C to +70°C**	Electrical Conductivity	**N/A**
Anti-Static	**N/A**	Weight	**2.67kgs**
Standard	**ISO22883**		

* For any deviation between metric and imperial spec, please refer to the metric spec.

Performance

Rolling Smoothness
Max. 5 points Score: 3

Quiet Operation
Max. 5 points Score: 4

Floor Surface Preservation
Max. 5 points Score: 4

Downloads

PDF **1233-EN-YJ2026111701.pdf**
Product Data Sheet

3D **1233-CN-YJ2026111701-d261117085436.rar**
3D drawings are for members only. Please log in to download.

© 2026 DERSHENG CO., LTD. All rights reserved.